

7. (Twice Amended) A tonneau cover apparatus for removable attachment about a top of a perimeter of a cargo box and tailgate of a pickup truck, the tonneau cover apparatus comprising:

a flexible cover;

an end plate;

33 a support frame for attachment to the cargo box; the support frame having first and second side rails forming opposite sides of the support frame, each of said first and second side rails including an end plate engagement member, each end plate engagement member being configured to engage and receive similar, but spaced apart, portions of the end plate, wherein the end plate is attached to an end of the flexible cover and the end plate is configured to cooperatively engage and pivot with respect to each end plate engagement member as the end plate passes into and out of a fixed stretching position, wherein the flexible cover is tensed when the end plate passes into the fixed stretching position; the end plate having an integrally formed radial engaging surface and each of the end plate engagement members having a radial receiving surface that engages at least a portion of the integrally formed radial engaging surface when the end plate pivots into the fixed stretching position.

Please amend claim 12 to read as follows:

12. (Twice Amended) A tonneau cover apparatus for removable attachment about a top of a perimeter of a cargo box of a pickup truck, the perimeter of the cargo box including a forward end, two opposing sidewalls and a tailgate, the tailgate being positioned rearward of the forward end and having an open position and a closed position, (the flexible cover having first and second ends,) the tonneau cover apparatus comprising:

BH a flexible cover having first and second ends;

a support frame for attachment to the cargo box, the support frame including two opposing side rails and a pair of end plate engagement members, one of which is secured to each of the respective opposing side rails rearward of the forward end when the support frame is attached to the cargo box of the pickup truck;

remove

edit claim 14

an end plate attached to the second end of the flexible cover, the end plate configured to cooperatively engage and pivot with respect to each of the respective end plate engagement members; wherein the end plate engagement members cooperate to engage the end plate when the first end of the flexible cover is operatively connected to the support frame forward of the respective engagement members, such that the end plate can pivot into and out of a fixed stretching position wherein the flexible cover is stretched to place a tension on the flexible cover; the end plate having an integrally formed radial engaging surface and each of the end plate engagement members having a receiving surface which engages at least a portion of the integrally formed radial engaging surface when the end plate pivots into the fixed stretching position; and

a locking member, the locking member operatively connected to the end plate rearward of each of the end plate engagement members when the end plate is in the fixed stretching position and movable between a first position and a second position when the end plate is in the fixed stretching position; wherein the locking member prevents the end plate from being disengaged from the fixed stretching position when the locking member is in the first position, and wherein the end plate can be disengaged from the fixed stretching position when the locking member is in the second position.

---

Please add the following new claims 17-18:

17. (Amended) A method of closing a tonneau cover apparatus, the method comprising the steps of:

(a) providing a tonneau cover apparatus for removable attachment about a top of a perimeter of a cargo box of a pickup truck, the cargo box including a front end, two sidewalls and a tailgate, the tonneau cover apparatus including:

a flexible cover having first and second ends;

an end plate; and

a support frame for attachment to the cargo box; the support frame having first and

second side rails forming opposite sides of the support frame, each of said first and second side rails including an end plate engagement member, each end plate engagement member being configured to engage and receive spaced apart portions of the end plate; the first end of the flexible cover being secured to the support frame forward of the respective end plate engagement members and the second end of the flexible cover being secured to the end plate; wherein the end plate is configured to cooperatively engage and pivot with respect to each end plate engagement member as the end plate passes into and out of a fixed stretching position in which the tonneau cover is in a closed position when the support frame is attached to the top of the perimeter of the cargo box, wherein the flexible cover can be correspondingly tensed and relaxed when the end plate passes into and out of the fixed stretching position; the end plate having spaced apart portions having integrally formed radial engaging surfaces that are configured and arranged to engage with and pivot with respect to the respective end plate engagement members; each of the end plate engagement members having a radial receiving surface configured and arranged to receive and engage the integrally formed radial engaging surface of the end plate;

(b) engaging the spaced apart portions of the end plate with the radial receiving surfaces of the respective end plate engagement members;

(c) pivoting the end plate in a first direction with respect to the end plate engagement members such that the spaced apart radial portions of the end plate slide against the integrally formed radial receiving surfaces until the flexible cover is tensed and the end plate is in the fixed stretching position.

---